



Kankakee River Flood and Sediment Management Work Plan




Siavash Beik and Robert Barr

Indiana Water Summit
August 15, 2019



Kankakee River Flood & Sediment Management Work Plan

- **Diagnose the Root Causes** of Erosion, Sedimentation, and Flooding through Detailed Field and Desktop Assessment
- **Communicate the Extent** of Existing Risks and Expected Trends (Changing Climate)
- **Identify Strategies** for Addressing the Issues in a System-wide Approach
- **Develop a Work Plan** for Implementing Various Strategies Specific to Each Area Within the Watershed (Main Stem Reaches, Laterals, Urban Areas, Ag Areas)




**A Joint Indiana – Illinois Effort
to Address a Legacy Problem
Facing Both States!**

RIVER HISTORY



1898 Extent of Grand Kankakee Marsh



(Kankakee Valley Historical Society)




Northwest Indiana Genealogical Society Collection




Kankakee River at the Indiana-Illinois State Line

KEY FINDINGS



Legend

-  Deepened/Widened
-  Dredged
-  Old Alignment






Kankakee River, Lake County, Indiana



Yellow River at Kankakee Fish and Wildlife Area

Transect #	Latitude	Longitude	Cross Section Area
14	41.24548334	-86.91959847	665.07 sq feet



Kankakee River, LaPorte and Starke Counties

Measured Channel Dimensions

Area = 538 ft²
 Width = 116 ft
 Mean d = 4.64 ft
 Max d = 7.0 ft

Predicted Bankfull Channel Dimensions

= 596 ft²
 = 132 ft
 = 4.4 ft
 = 6.2 ft



Kankakee River, Porter County, Indiana




Berm discontinuities along Kankakee River




Kankakee River downstream from Baum's Bridge, Porter and Jasper Counties

Recorded Peak Annual Discharges at Kankakee River at Shelby USGS Gage



Why are Peak flows and Average daily Flow Volumes Increasing?

- Increased rainfall depths and intensities due to climate change
- Uncompensated Impacts of urban development
- Increased agricultural tiling and surface draining projects (some in response to increasing rainfalls!)



Observed % Change in Total Annual Precipitation Falling in the Heaviest 1% of Events (1958 – 2016)



Extensive tile drainage

RECOMMENDATIONS

Addressing Systemic Flooding and Sedimentation in the Face of a Changing Climate

1. Adaptation

- ❑ Recognizing that flooding is going to occur again, taking steps to keep our risk exposure from increasing further, and reducing existing and future vulnerabilities to reduce pain and suffering


2. Mitigation

- ❑ Reducing the stressors to the system and to the Flooding and Sedimentation sources through common sense and feasible actions without adverse impact to others

Recommended Adaptation Strategies

➤ Provide Strategic Flood Protection to Critical Facilities & Key Infrastructure

- ❖ Strategic approach is needed due to inability to eliminate flooding everywhere
- ❖ Existing developments in floodplains are Legacy issues that are not related to or affected by the river corridor management strategies




Recommended Adaptation Strategies (cont.)

➤ Adopt NAI Stormwater Ordinance and Technical Standards for New Urban Development

- ❖ Comp Floodplain Storage, Channel Protection Volume, Detention,...

➤ Adopt NAI Standards for New Farm Drainage & Regulated Drain Projects

- ❖ Needed to offset the impacts of new surface ditching and subsurface tiling on increased runoff in the River



With Cover Crop



Without Cover Crop

Recommended Adaptation Strategies (cont.)


➤ Develop Flood Response Plans

- ❖ Flooding, such as that observed in 2018, cannot be prevented



➤ Develop Flood Resilience Plans


- ❖ Zone-specific strategies are needed to curb increase in flood vulnerability



Recommended Mitigation Strategies


➤ Reduce Sediment Supply from Yellow River Upstream of Knox

- ❖ Utilize nature-based methods to address erosion and stream instability



➤ Reduce Sediment Supply from Severely Eroded Kankakee Slopes

- ❖ Utilize bioengineering methods to keep sediment from falling into the River



Recommended Mitigation Strategies (cont.)

➤ Stop Maintaining and Strategically Breach Some Berms, Mitigating Flooding Using Setback Berms

- ❖ Connect river to its floodplain for improved conveyance, storage, and sediment distribution through Constructed Breaches




➤ Maintain Selected Reaches of Berms that are not Slated for Breaching

- ❖ Complete elimination of all river edge spoil pile berms is not practical in short term until conditions change



Recommended Mitigation Strategies (cont.)

- Purposefully remove and relocate infrastructure from berm-reliant areas
 - ❖ The end goal is to reconnect floodplains and give room to the river.
- Provide Zone-specific access to River for Managing Logjams
 - ❖ Improved bridge access for logjam removal is recommended at select locations





Recommended Mitigation Strategies (cont.)

➤ Restore Yellow River Sediment Transport Capacity Downstream of Knox

- ❖ Utilize nature-based concepts used in Pilot Project to promote effective sediment transport

➤ Remove Large wood in the most downstream reach of Yellow River


- ❖ Use of amphibious log removal equipment is preferred



Recommended Mitigation Strategies (cont.)


➤ Remove and/or Replace Restrictive Bridges

- ❖ Several active and abandoned bridges are interrupting the sediment flow and cause flow backup




➤ Construct off-line Retention or detention storage areas along Laterals

- ❖ Needed to offset increase in runoff due to past and ongoing land drainage activities in the watershed and/or increased rainfall



Summary of Work Plan Mitigation Components (Plan Sheets and Tables)



County	Extent of Improvement (River Mile)	DS Limit Description	US Limit Description	Recommended Action
Lake	59.4	State Line Road	State Line Road	Remove and replace State Line Road bridge [5.1.8]
Lake	59.4 - 73.5	State Line Road	US of I-65	Maintain existing setback berm [5.1.5]
Lake	65.7	-	-	Stabilize approximately 300 feet of unstable slope [5.1.2]
Lake	65.7 - 68.2	-	-	Construct breach in existing berm [5.1.6]
Lake	68.8	-	-	Construct breach in existing berm [5.1.6]
Lake	69.9	State Road 55	State Road 55	Improve access point on the upstream side of the bridge [5.1.3]
Lake	71.4	-	-	Construct breach in existing berm [5.1.6]
Lake	72.5	-	-	Construct breach in existing berm [5.1.6]
Lake	73	DS of I-65	DS of I-65	Construct breach in existing berm [5.1.6]
Lake	73.4	US of I-65	US of I-65	Construct breach in existing berm [5.1.6]
Lake	73.5 - 74.1	US of I-65	-	Construct new setback berm that ties into Clay St improvements [5.1.6]
Lake	74.1 - 74.2	-	Clay St	Construct improvements to Clay St to complete line of protection [5.1.6]
Lake	74.3	US of Clay St	US of Clay St	Construct breach in existing berm [5.1.6]
Lake	74.3 - 77.3	US of Clay St	-	Construct new setback berm that ties into existing berm [5.1.6]
Lake	74.8	-	-	Construct breach in existing berm [5.1.6]
Lake	75.0	-	-	Construct breach in existing berm [5.1.6]
Lake	75.7	-	-	Construct breach in existing berm [5.1.6]
Lake	76.4	-	-	Construct breach in existing berm and internal berms [5.1.6]
Lake	76.5	-	-	Construct breach in existing berm and internal berms [5.1.6]
Lake	77.2	-	-	Construct breach in existing berm and internal berms [5.1.6]
Lake	77.3 - 77.7	-	Lake - Porter Co Line	Maintain existing berm [5.1.5]

Other Alternatives Considered, but Not Recommended

- Dredging in the Kankakee and Yellow River
- Modification to the control section downstream of Momence Wetlands
- Converting berms to flood control levees
- Clearing trees from banks
- Increased tile drainage to reduce flooding
- Construction/Improvement of ditches to increase flood conveyance
- Berm improvements along tributaries

A Few Take Away Notes

❖ Most of the problems we face along streams in Indiana:

- Flooding
- Erosion and stream instability
- Sediment aggradation

❖ Often times, the root causes of these problems are:

- Stressors within the watershed
 - Increase in flows due to climate change
 - Increase in flow due to unwise urban development
 - Increase in flow due to farmers/drainage boards response to increased rainfall/runoff
- Mis-steps in attempts to fix problems in one location (dredging, tiling, berming, armoring banks) without an understanding of the entire stream system

❖ Given a changing climate we are facing, the only way out is embracing a system-wide , watershed-based approach of adaptation and mitigation that includes No-Adverse-Impact development decisions, Smart Growth resilience strategies, and Nature-based solutions.

QUESTIONS?

Siavash Beik, PE, CFM, D.WRE

Vice President, Principal Engineer

Christopher B. Burke Engineering, LLC

115 West Washington Street, Suite 1368 South
Indianapolis, IN 46204

317.266.8000 (office)

317.509.1673 (mobile)

Email: sbeik@cbbel-in.com

Robert Barr

Research Scientist

Center for Earth and Environmental Science

Department of Earth Sciences

IUPUI

317.278.6911 (office)

317.332.5463 (mobile)

e-mail: rcbarr@iupui.edu



**KANKAKEE RIVER
BASIN
COMMISSION**

6100 Southport Road Portage, Indiana 46368

